



Phono Solar Solar Panel Onyx Standard Module



Product Specifications

ELECTRICAL

Cell Type	Poly
Rated Power	260watt
Rated Voltage	30.4V
Rated Current	8.80A
Efficiency	15.67%

MECHANICAL

Dimensions	Length	1640mm
	Width	992 mm
	Depth	35mm

TEMPERATURE CHARACTERISTICS

Nominal Operation Cell Temperature	45°C +/- 2°C
Voltage Temperature Coefficient	-0.31%/k
Current Temperature Coefficient	+0.07%/k
Power Temperature Coefficient	-0.40%/k

Phono[®] Solar SUMEC

FEATURES

- Outstanding performance in weak light conditions
- Anti-PID [1]
- Excellent temperature coefficient giving higher yields in the long term
- IP68 connectors enhance the reliability of the PV system
- Positive current sorting
- 10-year product warranty
- 25-year performance warranty [2]
- Certified to withstand increased loads of up to 5400Pa

DURABILITY ASSURED

- Salt mist corrosion resistance
- Fire test resistance
- Ammonia corrosion resistance
- Blowing sand resistance
- Manufacturing facility certified by ISO 9001, ISO 14001 and OHSAS 18001
- Internal quality control has standards higher than both IEC and UL
- Product quality is assured through the use of branded components

[1] Anti-PID modules are only available upon request.

[2] In compliance with Phono Solar's warranty terms and conditions.



 1300 925 429

 info@caresolarsolutions.com.au

Collect. Store. Save.

caresolarsolutions.com.au

All care has been taken in the preparation of this material. Care Solar Solutions Pty Ltd accepts no responsibility for any loss, damage, costs or expense (whether direct or indirect) incurred by you as a result of any errors, omissions or misrepresentation of any information on this website.

